



Chargery Switching Power Supply Filter

Model	Input	Output Voltage and current	Output Power	Size/mm	Weight/g	Case	DC connector	display Module	APFC	Status	Certification
S1500	AC90-265V 50-60Hz	DC 10~30V 60A	1500W max.	252*145*68	2300	AL-alloy	3 pair of 4mm one pair 4.5mm banana female connector	YES	YES	avaiable	CE, CCC
S1200	AC90-265V 50-60Hz	DC 12~24V 50A	1200W max.	286*145*68	2300	AL-alloy	3 pair of 4mm banana female connector	YES	YES	avaiable	CE, CCC
S600	AC90-265V 50-60Hz	DC10~18V 33A	600W max.	223*106*55	1300	AL-alloy	2 pair of 4mm banana female connector	YES	YES	avaiable	CE, CCC
S400	AC100-240V 50-60Hz	DC 6~15V 25A	400W max.	145*106*55	800	AL-alloy	2 pair of 4mm banana female connector	YES	YES	avaiable	CE, CCC
S600PLUS	AC100-265V 50-60Hz	DC5~26V 40A	600W max.	223*106*55	1300	AL-alloy	2 pair of 4mm banana female connector	YES	YES	avaiable	CE, CCC
A1	AC100-240v 50-60Hz	DC 12V 1.5A	20W max.	80*53*35	130	ABS plastic	DC plug: 5.5*2.1	NO	NO	avaiable	CE, CCC
A6	AC100-240v 50-60Hz	DC 12V 6.0A	75W max.	130*55*30	430	ABS plastic	DC plug: 5.5*2.2	NO	NO	avaiable	CE, CCC
A12 V2.0	AC90-265v 50-60Hz	DC 12.0V 12.5A	150W max.	150*68*46	480	AL-alloy	4mm banana female connector	NO	NO	special offer	CE, CCC
A20	AC100-240v 50-60Hz	DC 14V 16A	250W max.	145*85*46	780	AL-alloy	4mm banana female connector	NO	NO	no	CE, CCC
A30	AC100-240v 50-60Hz	DC 14V 25A	350W max.	190*85*56	1200	AL-alloy	4mm banana female connector	NO	NO	no	CE, CCC

Appreciated for any suggestions on new product or improving present products

Contact us at admin@chargery.com.cn directly!!